

**In the Claims**

Please amend the claims as follows:

1. (Currently Amended) Device for connecting a wireless network to at least one other network comprising a bridge module for managing a plurality of ports for connecting to respective networks; characterized in that said device ~~it~~ comprises a ~~wireless network~~ link management module for managing associations; with an access point of a centralized wireless network, ~~of and~~ devices of networks connected to the bridge device other than the wireless network; wherein the bridge device is adapted to be a station of the wireless network.

2. (Previously Presented) Device according to claim 1, further comprising means for determining a spanning tree for all networks attached to the device, comprising means for enabling or disabling the determination of the spanning tree.

3. (Previously Presented) Device according to claim 1, further comprising means for updating filtering tables for respective connected networks, said filtering tables comprising information for determining whether a-message on a-network is to be forwarded to another network or not, said updating using a process by default, comprising means for enabling or disabling the default process.

4. (Previously Presented) Device according to claim 3, wherein said default process is based on analysis of source addresses in messages detected on a respective network, comprising means for enabling or disabling message detection based updating.

5. (Previously Presented) Device according to claim 3, further comprising means for updating a filtering table for a given network based on a device discovery process specific to said given network.

6. (Previously Presented) Device according to claim 3, wherein said default process is enabled for an Ethernet network.

7. (Previously Presented) Device according to claim 3, wherein said default process is disabled for a USB network.

8. (Currently Amended) Device according to claim 1, further comprising means for generating a message to said ~~wireless-network~~ link management module upon a filtering table amendment, said means for generating having an enabled state and a disabled state for each network.

9. (Original) Device according to claim 8, wherein said means for generating a message are enabled for an Ethernet network.